

Plugin Development: Views

Create your own templates for viewing pages in the plugin.

Templates are stored in the Views folder. SupportPro uses the `parent_template` and all templates should have a `.twig` file extension. For guidance on functions available within templates, please refer to the `Twig` documentation.

Templates used to show pages in the operator panel should start by extending the operator index template (`parent_template`), and it can also set the page title by using the title block. The content block is where you put what you wish to display. Below is an example template which makes uses of all these components.

Views/settings.twig

```
{% extends parent_template %}{% block title %}  {{ Lang.get('Plugins#HelloWorld::lang.hello_world')}}{% endblock %}{% block content %}  Your HTML here{% endblock %}
```

Most commonly you will just need the title and content blocks, but other blocks are available to set or fill other parts of the page. A full list of available blocks:

Block name	Description
meta	Additional <code><meta></code> tags for the page.

title	Sets the page title.
scripts_header	Used to add any additional CSS or other assets that should be loaded in the scripts_footer block.
header	Can be used to replace or extend the page header (navigation).
sidebar	Lets you add a sidebar, to the left of the content block.
precontent	Inserts data before the main content <div> attribute.
description	Adds a description below the page title.
content	The page content.
scripts_footer	Used to add any additional CSS, JS, jQuery or other assets.

The template can be returned from a controller method using:

```
TemplateView::operator('Plugins#HelloWorld::settings');
```

Templates used to show pages in the frontend should start by extending the frontend index template (parent_template), and it can also set the page title by using the title block. The content block is where you put what you wish to display. Below is an example template which makes uses of all these components.

Views/frontend.twig

```
{% extends parent_template %} {% block title %} {{ Lang.get('Plugins#HelloWorld::lang.hello_world') }} {% endblock %} {% block content %} Your HTML here {% endblock %}
```

Most commonly you will just need the title and content blocks, but other blocks are available to set or fill other parts of the page. A full list

of available blocks:

Block name	Description
title	Sets the page title.
meta	Additional <meta> tags for the page.
scripts_header	Used to add any additional CSS or other assets that should be loaded in the scripts_footer block.
header	Can be used to replace or extend the page header (navigation).
precontent	Inserts data before the main content <div> attribute.
breadcrumb	

Online URL:

<https://docs.supportpro.vn/article/plugin-development-views-211.html>