

Mail Security Policy

The use of merge fields in the operator panel is regulated by a strict policy for security reasons. This restricts what is possible for your help desk staff to do in terms of twig code and helps to keep the server secure.

For details on how to set the below configuration items, please read [\[redacted\]](#).

The security policy is made up of the following components:

Component	Documentation
Tags	[redacted]
Filters	[redacted]
Methods	Methods that can be called on class objects.
Properties	Properties that can be accessed on objects.

Create a new file `/config/production/mail.php`:

```
<?php return [ 'policy' => AppModulesCoreControllersMailer  
MailPolicy::policy()->toArray() ];
```

To add new [\[redacted\]](#) to the policy use the `addTags(array $tags):self` method:

```
<?php return [ 'policy' => AppModulesCoreControllersMailer  
MailPolicy::policy()->addTags(['do'])->toArray() ];
```

To add new ██████ to the policy use the `addFilters(array $filters): self` method:

```
<?php return [ 'policy' => AppModuleCoreControllersMailer
MailPolicy::policy()->addFilters(['abs']->toArray() );
```

To allow calling a new method on a class use the `addMethod(string $class, array $methods): self` method:

```
<?php return [ 'policy' => AppModuleCoreControllersMailer
MailPolicy::policy()->addMethod(IlluminateSupportCollection::class, [
'lazy']->toArray() );
```

To allow accessing a new property on a class use the `addProperty(string $class, array $properties): self` method:

```
<?php return [ 'policy' => AppModuleCoreControllersMailer
MailPolicy::policy()->addProperty(stdClass::class, ['foo']->toArray() );
```

Online URL: <https://docs.supportpro.vn/article/mail-security-policy-259.html>